



Adjustable Flow Handline Nozzles

Features

- Construction of Chemlite or Brass
- 100 PSI standard operating pressure
- Removable pistol grip
- Durable chrome plated ball shut off
- Change flow without changing pattern
- Flush without shutting down
- Large rubber handle
- Multiple pattern detents for positive pattern positioning combination fog and straight stream
- Conforms to all aspect of NFPA 1964 Standards



Suitable

- Refineries, Offshore Platforms, Chemical Plants, Storage Facilities, Fire Departments and more
- Suitable with water, In-Line Eductors, AFFF, AR-AFFF and Class "A" foam solutions

Accessories

- Repair Kit
- Quick Clamp-On Foam Tube

Part No:	Inlet	GPM	Length	Weight	Repair Kit	Material
MA10	1" NST	5-10-24-40	7"	4	RK1000	CHEMLITE
MA10P*	1" NST	5-10-24-40	7"	4	RK1000	CHEMLITE
MA15	1.5" NST	30-60-95-125	8"	4.5	RK1001	CHEMLITE
MA15P*	1.5" NST	30-60-95-125	8"	4.5	RK1001	CHEMLITE
MB15	1.5" NST	30-60-95-125	8.5"	8.5	RK1001B	BRASS
MB15P*	1.5" NST	30-60-95-125	8.5"	8.5	RK1001B	BRASS
MB15NPSH	1.5" NPSH	30-60-95-125	8.5"	8.5	RK1001B	BRASS
MB15NPSHP*	1.5" NPSH	30-60-95-125	8.5"	8.6	RK1001B	BRASS
MRA15	1.5" NST	30-60-95-125-150-200	10"	7	RK1002	CHEMLITE
MRA15P*	1.5" NST	30-60-95-125-150-200	10"	7	RK1002	CHEMLITE
MA25	2.5" NST	95-125-150-200-250	11"	7	RK1002	CHEMLITE
MA25P*	2.5" NST	95-125-150-200-250	11"	7.5	RK1002	CHEMLITE
MB25	2.5" NST	95-125-150-200-250	11"	13.5	RK1002B	BRASS
MB25P*	2.5" NST	95-125-150-200-250	11"	14	RK1002B	BRASS

CHEMGUARD
 204 S. 6th Ave • Mansfield, Tx 76063 • (817) 473-9964 • FAX (817) 473-0606

www.chemguard.com