



## *“Rattler” Hand Wheel Monitor*

### Features

- Corrosion Resistant Brass Construction
- Discharge 2-1/2” MNST
- Full 3” waterway allows flow up to 1250 GPM
- Single waterway low friction loss
- Full 360 degree rotation with positive twist lock
- Stainless steel ball bearings
- Grease fittings for all lubrication
- Red epoxy paint finish
- Vertical travel from 90 degree above to 60 degree below horizontal
- Easily adjustable in horizontal plane then locked in position by a locking mechanism
- Vertical travel is controlled by adjustable hand wheel



### Suitable

- Suitable with water and all types of foam solutions
- Suitable for Marine, Offshore, Industrial or other corrosive environments

### Accessories

- Truck Mount Kit Part #EF10041 (3” Flange, Gasket and Bolts)
- Monitor Nozzles
- Self-Educting Nozzles
- Stream Shaper & Stacked Tips

Part No:	Waterway	Inlet	Discharge	Material	Vertical Travel	Horizontal Rotation
CM-1250M-3	3”	3” Flange	2.5” MNST	Brass	90	360
CM-1250M-4	3”	4” Flange	2.5” MNST	Brass	90	360

**CHEMGUARD**  
 204 S. 6<sup>th</sup> Ave • Mansfield, Tx 76063 • (817) 473-9964 • FAX (817) 473-0606  
[www.chemguard.com](http://www.chemguard.com)