



“Brahma” Single Waterway Monitor

Features on CM-1250B-3 & CM-1250B-4S

- Corrosion resistant brass construction
- Flows up to 1250 gpm with minimum friction loss
- Grease fittings at each swivel joint
- Full 3” (76mm) waterway
- 2-1/2” MNST outlet
- Stainless steel ball bearings at each swivel joint
- 360 degree rotation w/positive lock
- Vanes at each elbow to reduce friction loss, improving range of stream
- Optional inlet flanges 3” or 4” flange

Features on CM-2000B & CM-2000H

- Corrosion resistant brass construction
- Flows up to 2000 gpm with minimum friction loss
- Grease fittings at each swivel joint
- Full 4” (100 mm) waterway
- Stainless steel ball bearings at each swivel joint
- 360 degree rotation w/positive lock
- Vanes at each elbow to reduce friction loss, improving range of stream
- 4” inlet flange and 3-1/2” MNST outlet

Suitable

- Suitable with water or all types of foam concentrates
- Suitable for Marine, Offshore, Industrial or other corrosive environment

Accessories

- Monitor Nozzles
- Self-Educting Nozzles
- Hydrant Mount Stand

| Part No: | Waterway | Inlet | Discharge | Material | Vertical Travel | Horizontal Rotation |
|-------------|----------|-----------|-----------|----------|-----------------|---------------------|
| CM-1250B-3 | 3” | 3” Flange | 2.5” MNST | Brass | 150 | 360 |
| CM-1250B-4S | 3” | 4” Flange | 2.5” MNST | Brass | 150 | 360 |
| CM-2000B | 4” | 4” Flange | 3.5” MNST | Brass | 150 | 360 |
| CM-2000H | 4” | 4” Flange | 3.5” MNST | Brass | 150 | 360 |

CHEMGUARD
204 S. 6th Ave • Mansfield, Tx 76063 • (817) 473-9964 • FAX (817) 473-0606

www.chemguard.com