



“Jackrabbit” Dual Inlet Ground Monitor

Features

- Durable, Lightweight Aluminum Construction
- Two 2-1/2" female swivel inlet x 2-1/2" male outlet
- Capable of flows up to 1250 GPM (4732 lpm)
- 3" flange adapter
- Full 3" (76 mm) waterway for low friction loss
- Compact folding base can be stored in any truck compartment or preconnected in the hose bed
- Legs lock in folded and deployed positions
- Safety stop at 30 degree above horizontal
- Stainless steel ball bearings at all rotation joints
- Liquid filled pressure gauge
- Grease fittings for lubrication
- Red paint finish
- Dual application-use as portable monitor or add the top flange for deck mount use
- High Volume:
 - 800 gpm(3028 lpm) in portable mode with double inlet
 - 1250 gpm(4732 lpm)in deck mount



Variables

- Interchangeable Flange Adapter
- Optional Package Supplied with Quad Stack Tips, Top Flange and Stream Shaper

Suitable

- Suitable for Fire Departments and Fire Appliance Applications
- Suitable for use with water or all types of foam solutions

Accessories

- Monitor Nozzles
- Self Educting Nozzles

Part Number	Description
CPM-1250	Monitor, Folding Base & Restraining Strap
CPM-1250-S	Monitor, Folding Base, Restraining Strap, 3" Flange Adapter, Stream Shaper & Stacked Tips
CPM-1250-3FA	3" Flange Adapter
CPM-1250-4FA	4" Flange Adapter
CPM-1250-FB	Folding Base
CN-ST	Quad Stacked Tips – 2", 1-3/4", 1-1/2", 1-3/8"
C-SS	Stream Shaper – 2-1/2" FNST x 2-1/2" MNST
CPM-1250-RS	Restraining Strap

CHEMGUARD
 204 S. 6th Ave • Mansfield, Tx 76063 • (817) 473-9964 • FAX (817) 473-0606
www.chemguard.com