



CHEMGUARD S-500

High Performance Amphoteric Fluorosurfactant

CHEMGUARD, INC. 204 South 6th Ave. Mansfield, Texas 76063 USA • 817-473-9964 • Fax: 817-473-0606 • www.chemguard.com

Product Description

Chemguard S-500 is a highly efficient short-chain perfluoro-based amphoteric fluorosurfactant. It provides surface tensions as low as 15 dynes/cm in water at very low concentrations. It also has excellent dynamic surface tension properties, allowing for rapid attainment of low equilibrium surface tensions. Chemguard S-500 imparts excellent wetting, spreading, leveling, and flow control properties on various types of water-based as well as solvent-based systems. Its extremely low equilibrium surface tension in conjunction with excellent dynamic surface tension properties makes it ideal for coating formulations designed for difficult to coat, low surface tension substrates. Its amphoteric nature allows S-500 to be unsusceptible to the differences in pH, which provides excellent hard water resistance.

Attributes

- Non-flammable
- Excellent dynamic surface tension properties
- Excellent for wetting difficult to coat surfaces
- Excellent foamer
- Excellent replacement for **FS-500** and **FS-50**
- Composed of short chain C-6 perfluoro telomer

Typical Properties¹

Appearance	Clear, dark amber liquid
Composition	27% actives, 18% solvents, 55% water
Density	1.18g/ml at 25°C
pH	5.5-7.0
Aqueous Surface Tension dynes/cm (mN/m), 25°C (77°F), Kruss Tensiometer K100	
0.1% Actives	15.0-16.5
0.01% Actives	15.5-18.5
Flash Point	>93°C (200°F) Pensky-Martens Closed Cup
Freezing Point	-4°C

¹ Not for specification purposes.

Typical Applications

Chemguard S-500 is a dilute solution composed of 27% active fluorosurfactant in a water and solvent miscible diluent. Typical uses include leveling and anti-static agents for photographic coatings, floor polishes, paints and coatings, adhesives, inks, waxes, caulks, pickling and plating baths, and in solvent extraction of metals in aqueous solutions. Applications of Chemguard S-500 are generally those in which typical hydrocarbon surfactants are found to be inadequate.

Fluorosurfactants such as Chemguard S-500 are much more chemically stable than typical hydrocarbon surfactants, particularly in the presence of acids, alkalies, or heat.

Recommended application rates depend on the formulation makeup but typical levels of 0.05% to 0.4% are common. The charts below will aid in determining the amount of Chemguard S-500 that is required for a targeted level of active surfactant concentration to achieve the degree of surface tension reduction. The ideal method for determining the proper level is to screen several ranges of concentrations to achieve the desired effect on the surface tension and wetting action.

Solubility

Chemguard S-500 is soluble in water and most organic solvents. The chart below is an example of the solubility of S-500 in many solvent systems. Chemguard can assist in determining solubility in any system.

Solvent	Grams of Chemguard S-500/ 100 grams of solvent
Distilled Water	>2
Isopropanol	>2
1:1 Water/Isopropanol	>2
Methyl Alcohol	>2

All values measured at 25°C

Storage and Shelf Life

Chemguard S-500 should be stored between 0°C and 50°C. Some solids begin to separate at temperatures below -4°C over time. If frozen or if solids separate, warm to room temperature before use. Freezing and thawing will not affect the properties or performance.

Shelf life is at least five years if stored tightly sealed in the original container at temperatures below 50°C (151°F).

Health and Safety

Chemguard does not recommend this product for use in applications involving repeated exposure to skin contact, inhalation, or ingestion.

Chemguard fluorosurfactants are based on telomer synthesis. No PFOS, no PFOA, and no derivatives that decompose to them are used in the manufacturing process. Chemguard S-500 is composed of predominately six carbon (greater than 98%) and shorter perfluoro chains with no known pathway of decomposing to PFOS or PFOA.

Please refer to the material safety data sheet (MSDS) for recommended disposal, handling, and protection information.

SELLER MAKES NO REPRESENTATION OR WARRANTY, EXPRESSED OR IMPLIED. INCLUDING MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. No statements herein are to be construed as inducements to infringe upon a relevant patent. Under no circumstances shall the Seller be liable for incidental, consequential or indirect damages for negligence, breach of warranty, strict liability, tort or contract arising in connection with the product(s). Buyer's sole remedy and Seller's sole liability for any claims shall be Buyer's purchase price. Data and results are based on controlled or lab work and must be confirmed by Buyer by testing for its intended conditions of use.